



Produktinformation		Product information	
Produktbeskrivning: Nordic R H4b Ground med Bullerskärm Nordre		Product description: Nordic R H4b Ground with Noise barrier Nordre.	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007/A2:2012	
Kapacitetsklass	H4b	Containment level	H4b
Ständaravstånd (m)	2.0	Post spacing (m)	2.0
Norm. fordonsinträngning (klass)	VI5	Norm. vehicle intrusion (class)	VI5
Norm. fordonsinträngning (m)	1.4	Norm. vehicle intrusion (m)	1.4
Norm. arbetsbredd (klass)	W5*	Norm. working width (class)	W5*
Norm. arbetsbredd (m)	1.5*	Norm. working width (m)	1.5*
Norm. dynamisk utböjning (m)	1.1	Norm. dynamic deflection (m)	1.1
Skaderiskklass	A	Impact severity level	A
Motstånd mot snöplogning (klass)	4	Resistance to snow removal(class)	4
Harmoniserad standard: EN14388:2005/AC:2008		Harmonised standard: EN14388:2005/AC:2008	
Vindlast (kN/m ²)	1.4	Wind load (kN/m ²)	1.4
Snölast (kN)	15	Snow load (kN)	15
Beständighet: Varmförsinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	
Ständaravstånd (m)	2.0	Post spacing (m)	2.0
Konstruktionsbredd (m)	0.61	Construction width (m)	0.61
Konstruktionshöjd (m)	2.0	Construction height (m)	2.0

* Värde för räcke / Value for safety barrier